

M2M
SERVICES

SIMPLICITY.
APPLIED.

UNIVERSAL SOLE PATH COMMERCIAL FIRE COMMUNICATOR



MQ03-LTE-FIRE



MULTIPLE CARRIERS IN A SINGLE DEVICE

AT&T and T-Mobile LTE with fallback to 3G/4G



FAST AND EASY INSTALLATION

with any panel using Contact ID and SIA



RELIABLE DATA REPORTING

to any Central Station from coast to coast



IMPROVED RECURRING REVENUE

Flat-rate low monthly fees for improved profitability

**MQ03-LTE-FIRE**

MAIN FEATURES

REPORTING FORMATS – Dial Capture Interface supporting Contact ID, SIA and Pulse 4+2

EXCEPTIONAL REDUNDANCY – Dual-SIM for AT&T/T-Mobile. Optional reporting through LAN

SUPERVISED CONNECTIVITY – 5 minute polling

ADMIN PORTAL – Online 24/7 device management & real-time status monitoring of user accounts

FULL EVENT REPORTING – Reliable reporting to any Central Station

INSTALLER MOBILE APP – Real-time on site communication diagnostics and device configuration

UNIVERSAL PANEL COMPATIBILITY – Works on 12 to 30 VDC, supporting wide range of fire panels

SPECIFICATIONS

- Multi-band LTE 700/850/1700/1900 MHz
- 3G/4G 850/1900 MHz fallback
- 2 inputs & 2 outputs (programmable)
- Supply voltage: +12 to +30 VDC
- Consumption: Standby 50mA, Peak 200mA
- Dimensions: 2.48" x 3.54" x 1.26"
- Weight: 2.65oz without antenna

CONFORMS TO UL STANDARDS

- UL 864 - for Control Units and Accessories for Fire Alarm Systems, listed as a sole path cellular
- UL 1610 - for Central-Station Burglar-Alarm Units

RCONTROL ADMIN MOBILE APP

